


Enclosed AC/DC Switching Power Supply



Features

- Slim and Low Profile
- Protections :
Short circuit / Over voltage / Over current
Over temperature
- Energy Efficiency $\geq 92\%$ ~95% depends on models
- MTBF > 50,000 hours
- Fanless and Conduction-cooled Design
- Withstand 300VAC surge input for 5 seconds
- Built-in Active PFC Function
- DC OK Relay Contact
- LED Indicator

EP1500 U - XX YY

- U:** Output range
- XX:** Specified output voltage, i.e. 12 is 12VDC
- YY:** Differential segmentation

General Specification

OUTPUT

MODEL No.	MAX. OUTPUT POWER (W)	OUTPUT VOLTAGE (Vo)	MIN. LOAD (Io)	MAX. LOAD (Io)	LOAD REGULATION	LINE REGULATION	RIPPLE & NOISE
EP1500A	500.4W	12V	0A	41.7A	$\pm 0.5\%$	$\pm 0.5\%$	200mV
EP1500B	501.6W	24V	0A	20.9A	$\pm 0.5\%$	$\pm 0.5\%$	240mV
EP1500C	500.4W	36V	0A	13.9A	$\pm 0.5\%$	$\pm 0.5\%$	360mV
EP1500D	501.6W	48V	0A	10.45A	$\pm 0.5\%$	$\pm 0.5\%$	360mV

NOTE:

- 1 : Ripple & Noise is measured by using 20MHz bandwidth limited oscilloscope and terminated each output with a 0.1uF ceramic capacitor & parallel with 47uF aluminum capacitor at full load and nominal line.
- 2 : Line regulation is defined by changing $\pm 10\%$ of input voltage from nominal line at rated load.
- 3 : Max. Power (W) $\geq V_o \times I_o$

INPUT

- Input Range 100 to 240VAC
- Frequency 50 to 60Hz
- Input Current $\leq 5A$
- Inrush Current $\leq 60A@230VAC$, Cold start
- Hold Up Time $\geq 8.3ms$
- Turn On Time $\leq 1s$


PROTECTION

- Short Circuit Protection Auto Recovery
- Over Current Protection Auto Recovery
- Over Voltage Protection Latch-off
- Over Temperature Protection Auto Recovery


ENVIRONMENT

- Operating Temperature -30 to 70°C
- Storage Temperature -40 to 85°C
- Operating Humidity 20% to 90 %
- Storage Humidity 10% to 95 %

DERATING CURVE



MECHANICAL



- Mechanical Size: 232L x 81W x 33H (mm)

- Pin Assignment:

AC Input terminal(TB1): (DEGSON)DG28C-B-03P

Pin No.	Assignment
1	AC/L
2	AC/N
3	⊥

DC output terminal(TB2, TB3): EDAC terminal

Pin No.	Assignment
TB2	+V
TB3	-V

- Weight: 1800g

SAFETY

- Complied with UL 62368-1, CAN/CSA C22.2 No. 62368-1, TUV EN 62368-1, CB IEC 62368-1, FCC Part 15B, CE EMC(EN 55032+EN 55035)